Automatic Letter Opener Model 3068



Milling Cutter Technology

Protects the contents from being cut or damaged. Removes up to 3mm (1/8") of the envelope edge. The removed material is in the form of tiny chips, which are deposited in the waste bin. Creates a soft, feathered edge opening, which prevents paper cuts and gives easy access to the contents.

Mixed Thickness Separator

This separator design ensures that only one envelope passes through the machine at a time maximizing separation and improving cut quality.

High Speed

Opens up to 32,000 envelopes per hour. Opens mixed mail, from the smallest to the largest, completely. Opens up to 6mm (1/4") thick envelopes. Entire system built to handle large flats and envelopes.

Simple and Reliable

High degree of operational reliability

Heavy Duty

Solid metal construction throughout. Made of steel using the highest quality of components. Has two motors for better performance and a longer life.

Standard Features:

Resettable counter, batch counter, rate counter, lifetime counter, on demand feeding, on delay feeding, milling cutter on/off, variable speed

Options:

12mm (0.5") print head for date / time / bitmap printing

Specifications:

 Length: 1070mm (42in)
 Depth: 750mm (30in)
 Height: 1065mm (42in)
 Weight: 90kg (200lbs)

 Power: 120VAC - 5.00A or 230VAC - 3.00A
 Envelope Size: All sizes and types. Maximum Thickness 6mm (1/4")
 Depth of Cut: From 0 (no cut) up to 3mm (1/8")

 Feeder Capacity: Approx. 100 envelopes
 Receiving Tray Capacity: Approx. 100 envelopes

 Theoretical speed: 32,000 envelopes per hour
 Production speed: 14,000 envelopes per hour

 Stand and Waste Bin: Included.
 (If you have a trained octopus as an operator, revert to the theoretical speed)



(800) 560-2242 Email: sales@abe-online.com