


intimus 175 In the Department

Professional Data Shredders – a Synthesis of Technology, Performance and Design. All intimus® shredders are built from durable, precision engineered, high-performance components, designed for a long life of high volume usage. The product range covers all requirements from day-to-day office use up to High Security Shredding machines in use for destruction of classified material in line with all current legal requirements such as DIN 66399 or NSA 02/01. intimus® shredders carry various features which make them unique in user-friendliness and operating efficiency.



W/D/H 66 x 56 x 105 cm

- Low noise level
- Integrated Auto Reverse Function for easy removal of paper jams
- Illuminated indicators for stand-by, basket full, door open and paper jam
- Sealed dust-free design with robust wooden cabinet
- Mounted on rollers for flexible use



*CP5,
CP6 / 2



130 CP5 | 130 CP6 | 130 CP7

Ecologic

i-control®

DLS

Model	Shred size		Security level DIN 66 399	Shredding capacity*		Cutting speed	Throughput**		Also shreds:			
	mm	l		70 g/m ²	80 g/m ²		70 g/m ²	80 g/m ²	CD	DD	FD	FD
175 SC2	5.8	175 10+	2 - 2 2 ⁺ - -	65-70	55-60	0.12	1,697	1,455	✓	✓	✓	✓
175 SC2	3.8	175 10+	2 - 2 2 ⁺ - -	40-45	35-40	0.12	1,091	970	✓	✓	✓	✓
175 CC3	4 x 40	175 10+	4 - 2 3 ⁺ - -	45-50	38-43	0.13	1,111	949	✓	✓	✓	✓
175 CC4	1.9 x 15	175 10+	5 2 4 5 ⁺ - -	25-30	22-26	0.13	606	525	✓	✓	✓	✓

* only floppy disks / ID cards

High Security Shredder (optionally available with automatic oiler)

175 CC5	0.8 x 12	175 10+	6 3 - - - -	15-17	13-15	0.15	515	455	-	-	-	-
175 CC6	0.8 x 4.5	175 10+	7* 3 - - - -	8-10	7-9	0.23	465	418	-	-	-	-

* NSA approved (NSA / CSS EPL 02/01)

Optional Equipment	Packing unit	Art. No.	Shredder oil for CC-models	Packing unit	Art. No.
PE bags intimus 130 and 175	50 pieces	99952	Bottle at 110 ml	6 bottles	88035
Catchbasket intimus 175	1 piece	85829	... for models with oiler, 2 litres	1 bottle	91869

* based on 70 g/m² A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

** theoretical average performance paper/min