DESTROYIT® 4606

Space saving High Capacity shredder with automatic oiler and unique feed hopper for bulky material. Equipped with a conventional feed slot for flat paper stacks.

Security level P-3	6 x 50 mm cross-cut (1/4 x 2 inches)
Sheet capacity*:	50-60*
Security level P-5	2 x 15 mm cross-cut (3/32 x 5/8 inches)
Sheet capacity*:	32-37*

*Certified using 8.5" x 11" 20 lb. bond and recommended power supply.



Open tilting feeding hopper for crumpled paper. Feeding paddle for effective insertion of crumpled paper into the cutting head. Second feed opening located under the hopper for flat paper and computer printouts with automatic start/stop via a photo cell. EASYSWITCH – intelligent multifunction control element indicating the operational status of the shredder with varying color codes and back-lit symbols. Electronic control prevents over feeding: automatic reverse and re-feeding in case of paper jams. Foldaway feeding table. Main switch and emergency cutoff switch. Robust shredding heads with special hardened cutting shafts made of high quality steel, resistant against soft metal objects. Automatic oil injection on the cutting shafts during shredding operation for constant high shred performance. Automatic standby after 30 minutes. Powerful three phase motor with thermal motor protection. Front door and mobile shred bin for easy removal of the full shred bag. High volume container for the shredded material. Tilting hopper for cleaning access. Automatic stop when hopper or front door is opened, or when the shred bin is full. Mobile on casters.

Specifications

Shred volume, gallons	61
Feed opening, inches	18
Electrical requirements, volts	220, 3 phase
Maximum horsepower	7 1/3
Product dimensions (D x W x H), inches	30 x 29 x 67
Product weight, pounds	558



WWW.ABE-Online.com TEL: 800-560-2242







*High Capacity models have a 1 year limited warranty. All technical data is approximate and subject to change. © MBM Corporation, 10/2018

DESTROYIT® 4606

Features



EASY-SWITCH

Ease of operation: intelligent multifunction switch with integrated optical signals indicating the operational status.



FOLD-OUT FEED TABLE The fold-out feed table is used for feeding flat paper stacks. Start and stop functions are controlled by photo cell.



ELECTRONIC OIL INJECTION The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a constantly high shred performance.



ELECTRONIC SAFETY FEATURES Should a jam occur, the hopper can be tilted back to clear the jam. Motor power is automatically cut during this operation.



BULK PAPER SHREDDING Special rotating paddles are used to feed bulky materials into the cutting unit.



MOBILE SHRED BIN Caster-mounted shred bin is easily removable through the front cabinet door. Shredder stops automatically when door is opened.



CORPORATION

*High Capacity models have a 1 year limited warranty.

CORPORATION



WWW.ABE-Online.com TEL: 800-560-2242



*High Capacity models have a 1 year limited warranty. All technical data is approximate and subject to change. © MBM Corporation, 10/2018