



The World Leader
In Data Elimination

DATA ELIMINATOR

HD-2XT

High-Speed and Economical Degausser

HD-2XT High-Speed Degausser

Garner's high-speed and economical hard drive degausser is made with the same high quality components as our other products. This compact, lightweight degausser generates a 10,000 gauss magnetic field to permanently erase all data from hard drives and tape in 8 seconds.

Easy to use, simply place the media in the drawer. Closing the drawer automatically starts the degauss cycle.

The HD-2XT is designed to integrate with Garner's exclusive IRONCLAD® Erasure and Destruction Verification System with JPG image capture for complete, permanent and verifiable data elimination. Only Garner offers complete hard drive erasure with JPG images and reports of degaussed hard drives, providing the best audit trail and proof-of-erasure and destruction reports available.

Secure and Compliant

The HD-2XT will help you meet government and industry standards requiring complete erasure of sensitive data prior to disposal, including:

- **CCPA (California Consumer Privacy Act)**
- **DoD Up to Secret Classification**
- **GDPR (General Data Protection Regulation)**
- **GLBA (Gramm-Leach-Bliley Act)**
- **HIPAA (Health Information Portability and Accountability Act)**
- **IRS 1075**
- **NIST SP 800-88r1**
- **PCI DSS 3.2 (Payment Card Industry Data Security Standard)**
- **PIPEDA (Personal Information Protection and Electronic Documents Act)**
- **TAA**



HD-2XT Features

- Economical and durable
- Generates 10,000+ Gauss (1 Tesla) magnetic field for complete erasure of hard drives and tape
- Complete data erasure in 8 seconds
- LCD numerically displays gauss level after each cycle
- Erases up to 1,920 (1.8 in.), 960 (2.5 in.), and 240 (3.5 in.) drives per hour
- Erases working and non-working hard drives
- Continuous duty - no cool down between cycles
- Office quiet
- CE certified, TAA compliant
- Portable, lightweight (34 lbs)

HD-2XT Erasure Verification

Built-in field verification checker: system and on-board diagnostics confirm the magnetic field strength of every erase cycle, ensuring complete erasure.

LCD display: Provides numerical value of gauss field strength after each cycle.

SCAN-1X Media Destruction Report software and scanner (option): Creates a media destruction report complete with date, time, user ID, serial number, and erasure verification of each degauss cycle.

IRONCLAD Integrated Auditing System (option): Generate the ultimate proof-of-erasure and destruction reports with JPG images of the media and numerical documentation of the gauss field strength.

IRONCLAD® Verification

Add the IRONCLAD Integrated Auditing System to your HD-2XT. IRONCLAD captures a JPG image of the media and automatically generates a Certificate of Erasure and Destruction, including the crush depth of the PD-5 physical destroyer.

IRONCLAD documents and records the gauss field strength of each erase cycle.



Packages

Configure a system to match your needs. Pair the HD-2XT high-speed degausser with our PD-5 NSA-listed destroyer or PD-4 NSA-listed destroyer.



*Data Eliminator Cart Package
(RCC-25SSD IRONCLAD with optional bins)*



*Degauss Destroy Recycle Workstation
(DDR-25SSD IRONCLAD shown)*

Optional Accessories



IRONCLAD Erasure Verification System



SCAN-1X



*CASE-HD2XIC
MIL SPEC Shipping Case*



Recycle Bin



"Degaussed" Labels



Media Bins

| SPECIFICATIONS | |
|--------------------------------------|---|
| Part Number | HD-2XT, HD-2XTE |
| Certifications/Listing | CE • TAA |
| Magnetic Field | 1 Tesla (10,000 Gauss) nominal |
| Erasure Verification | IRONCLAD optional SCAN-1X optional |
| Charge Time | 8 seconds (nominal) |
| Throughput (Hard drives per hour) | Up to 1920 (1.8 in.) Up to 960 (2.5 in.) Up to 240 (3.5 in.) |
| Media | Hard drives: Laptop, standard, network up to 1.25 in. in height Tape media: All LTO, all DLT, AIT, 2590 Series, 8mm, and others |
| Power | HD-2XT: 100~125VAC ±5%, 50/60 Hz HD-2XTE: 90~250VAC ±5%, 50/60 Hz |
| Power Consumption | During standby: 17W During charge: 145W (avg) At the time of erase: 17W |
| Degausser System | Capacitive discharge |
| Duty Cycle | Continuous |
| Media Drawer Capacity (HxWxD) | 1.25 x 4.3 x 5.9 (in.) 31.8 x 108 x 148.6 (mm) |
| Temperature | 41°F - 104°F (5°C - 40°C) |
| Humidity | 10%H - 40%H without condensation |
| Weight | 34 lbs. (15.44 kg) |
| Size (HxWxD) | 6 x 17.8 x 13.3 (in.) 151.1 x 450.9 x 337.8 (mm) |
| Warranty | HD-2XT: One-year manufacturer's limited warranty standard, optional three-year limited warranty available. HD-2XTE: One-year manufacturer's limited warranty standard. |
| Made in U.S.A. | By Garner Products, Inc. |

Note: Hard drives and some tapes are not reusable after being degaussed.