



WWW.ABE-Online.com TEL: 800-560-2242



INTIMUS 16.50 SMARTSHRED HEAVY DUTY SHREDDER SOLO VERSION

- Smart with PLC control
- ► 19.7" working width; suitable for all standard paper sizes
- **▶ Wide EMERGENCY STOP BAR**
- Integrated Oilingsystem





HIGH-PERFORMANCE LARGE DOCUMENT SHREDDER

For decades, the intimus® heavy duty shredders have proven to be centrally positioned pieces of equipment for the privacy-friendly disposal of disused media. The model range offers variations that can handle up to 550 sheets/h or even complete folders in a single operation. The spacious feed table with integrated infeed conveyor belt provides controlled, effortless, safe and fast loading. The shredded material is collected in large-scale, mobile or swing-out containers under the cutting mechanism. The shred-press combinations are coupled to a baler for immediate fully automatic compaction of the cut material into compact bales. Reduction effect compared to the loose collection of the cuttings is about 70%.



FEATURES

- 500 mm working width; suitable for all standard computer formats
- Feeding via conveyor belt
- Container is removed from the operator side
- Shredder can be installed next to a wall
- Audible "bin full" alarm, with simultaneous automatic stop of the shredding process
- Wide EMERGENCY STOP BAR on receiving table for immediate stop in an emergency
- 450 I collecting bin supplied as standard equipment



PLC CONTROL

- More Information
- Exact error display
- Display when service would be beneficial
- Useful information such as operating hours or blocking notification
- All possible accessories are saved in the software and only need to be activated
- Via an USB-stick or a SD card the customer can change the software of the PLC
- The display can also be adjusted to customer requirements



SPECIFICATIONS		
Shred size	0.39" x 2.76" (10 x 70 mm)	0.24" x 1.97" (6 x 50 mm)
Bin volume	118.9 gal / 88.2-121.3 lbs (450 l / 40-55 kg)	118.9 gal / 88.2-121.3 lbs (450 l / 40-55 kg)
Working width	50+ persons	50+ persons
Security level DIN 66399	P-2/ 0-2 / T-2 / E-2	P-3/ 0-3 / T-3 / E-2
Shredding capacity*	470-520 sheets 70 g/m ²	300-330 sheets 70 g/m ²
	400-450 sheets 80 g/m ²	260-290 sheets 80 g/m ²
Cutting speed	78.7 ft/s (0,24 m/sec)	78.7 ft/s (0,24 m/sec)
Throughput**	1212.5 - 1322.8 lbs/h	1058.2 lbs/h
	(550-600 kg/h)	(480 kg/h))
Noise Level	61 dB	61 dB
Also shreds:	7 0 = # I	7 Ø 🗇 🖽
Weight	1600.6 lbs (726 kg)	1600.6 lbs (726 kg)
Dimensions (WxDxH) * based on 70 g/m2 A4 paper. Sheet capacities vary	47.2" x 76.8" x 61"	47.2" x 76.8" x 61"
	120 x 195 x 155 cm	120 x 195 x 155 cm



^{*} based on 70 g/m2 A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

** theoretical average performance paper/min